

# Technical Data Sheet

1. Type	E-100 CONTACT ADHESIVE (ORIGINAL)
2. Usage	For bonding laminates to table top, decorative metal cladding in construction industries, rubber, leather, cork, polyurethane foam, fibreglass, aluminium foil, interior decoration and furniture.
3. Application	Apply by scrapper, brush or suitable roller.
4. Physical Appearance	Viscous liquid
5. Material Composition	Synthetic elastomer / Resin in organic solvents.
6. Density	0.83 - 0.86 g/ml
7. Colour	Yellowish to light brown
8. Viscosity	3000 - 4000 cps
9. Total solid	24.0 % +/- 1% w/w
10. Tack life	5 - 30 minutes depending on surface porosity.
11. Caution	<p>The solvents in this product are highly flammable. Use only in well ventilated area. Avoid open flame, heat, spark, ignition source, hot work or static discharge. <i>The above hazard applies when the product is at its wet stage due to the presence of solvent that act as a carrier.</i></p> <p>THIS PRODUCT IS HARMLESS AND NON FLAMMABLE AFTER APPLICATION AND WHEN THE ADHESIVE IS CURED.</p>
12. Storage	Keep lid tightly closed after used and store in cool, dry and well ventilated area away from any possible heat or spark.
13. Shelf life	12 months from manufacturing date.

Effective date : 1<sup>st</sup> August 2020

The above information is given in good faith and to the best of our knowledge. We makes no warranty or guarantee of results and assume no obligation or liabilities for the use of any product mentioned herein. We expect person(s) receiving this information to exercise their independent judgement or consult with a competent professional to determine the safety and appropriateness of this material for a specific use.