



技术资料

Version number 28/3/2013

| | Durabond PA 5547LV |
|----------------------|--|
| Type of Adhesive | Aqueous polymer dispersion |
| Product Benefits | Durabond PA 5547LV is a waterbased adhesive with good adhesion on |
| | wood, chipboard and MDF board and paper |
| Typical Applications | General use for chipboard to chipboard lamination and wood to wood |
| | lamination (for furniture assembly), paper overlay (such as PU paper and |
| | MB paper to chipboard or MDF board) and paper to paper lamination. |

Typical Properties

| Colour | Off White | |
|---|---------------------|--|
| Odor | Characteristic | |
| Shelf life | 12 months | |
| рН | 6.0 – 7.5 | |
| Viscosity (Brookfield RVT 6/20, @ 28°C) | 12,000 – 20,000 cps | |
| Solid content | 38.0 - 44.0% | |

Application Instructions Durabond PA 5547LV is ready for use. For best result, it is recommended to be used within the shelf life. Surfaces to be glued must be clean, dry and free from dust, oil, grease and dirt. Product should be stir before use and do not mix with other adhesives. **Cleaning Instructions** Whenever possible, clean up the adhesive before it dries using water. If dry, use water or by mechanical scrapping. **Typical Packaging** Please contact local Sales Office for available packaging options. Storage Conditions Product should be stored in closed original containers in a clean dry place and out of direct sunlight where the temperature is between 10 - 35 °C. **Disposal Advice** Please refer to the MSDS for disposal instructions. Safety Advice Please refer to the MSDS for safety advice

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia Tel: +61 1800 423 855 customer.service@hbfuller.com China & Hong Kong Tel: +86 20 82068291 cs.china@hbfuller.com Indonesia Tel: +62-21-5307232/33 Korea Tel: +82 2 786 8296 cskorea@hbfuller.com Malaysia Tel: +603 3345 5200 New Zealand Tel: +64 800 555 072 customer.service@hbfuller.com
 Philippines

 Tel: +63 2 5194073

 Taiwan

 Tel: +886 2 26033385

 Thailand

 Tel: +66 2 3757442

 Vietnam

 Tel: +84 8 22225588

